


# NASA TECH BRIEF



NASA Tech Briefs are issued to summarize specific innovations derived from the U.S. space program, to encourage their commercial application. Copies are available to the public at 15 cents each from the Clearinghouse for Federal Scientific and Technical Information, Springfield, Virginia 22151.

## Integrated Metal Transistor Leads



### The problem:

In the conventional manufacture of transistors, large pellet bonding terminals are required as targets for the bonded lead wires and contribute to device capacitance. Additionally, the incidence of bonding lead wires having different lengths is a factor that results in an increased inductance to those emitters being fed by the longer wires and subsequent degeneration in their injection.

### The solution:

A technique that makes the metal leads integral to the transistor wafer. This appreciably reduces capacitance in the device, thereby increasing its efficiency.

### How it's done:

After defining the base contacts in the oxide and depositing Au in the openings, the wafer is again coated with a photoresist and an opening is made in the resist. A layer (60,000–100,000 Å) of Al is then evaporated over the surface of the wafer, forming the composite structure shown in the left figure. The metal is next coated with photoresist and defined by electrolytic etching to produce a pattern on each pellet in the form shown in the center figure.

The wafer is next scribed on each side by standard scribing techniques to assist separation of the indi-

vidual pellets, accomplished by placing the wafer in hot benzene sulphuric acid which dissolves all the photoresist, leaving pellets like that shown in the right figure.

### Notes:

1. Measurements made on TA2675 devices fabricated with integral leads and fabricated with wire-bonded leads showed a 26% capacitance reduction in the integral lead device.
2. In using integral leads, length of the bond wires is controlled by photolithographic techniques, assuring equal inductance to the pellet.
3. No additional documentation is available. Inquiries may be directed to:

Technology Utilization Officer  
Goddard Space Flight Center  
Greenbelt, Maryland 20771  
Reference: B68-10518

### Patent status:

No patent action is contemplated by NASA.

Source: E. T. Casterline and D. R. Carley  
of Radio Corporation of America  
under contract to  
Goddard Space Flight Center  
(GSC-90536)  
Category 01